


Ring Tongues - Nylon Insulated with Insulation Grip 26-24 AWG


Product Number†	UPC (054007-)	Wire						Barrel Length	Barrel I.D.	Maximum Insulation Diameter	Terminals per:		
		Range (AWG)	Stud Size	W	C	L	E				Thickness	Carton	Case
MNG24-0RK	00969	26-24	0	0.14	0.12	0.47	0.40	0.020	0.13	0.030	0.093	—	1000
MNG24-2RK	00970	26-24	2	0.14	0.12	0.47	0.40	0.020	0.13	0.030	0.093	—	1000
MNG24-4RX	11318	26-24	4	0.20	0.21	0.60	0.49	0.020	0.14	0.030	0.093	100	500
MNG24-4RK	00971	26-24	4	0.20	0.21	0.60	0.49	0.020	0.14	0.030	0.093	—	1000
MNG24-6RX	49587	26-24	6	0.20	0.21	0.60	0.49	0.020	0.14	0.030	0.093	100	500
MNG24-6RK	00972	26-24	6	0.20	0.21	0.60	0.49	0.020	0.14	0.030	0.093	—	1000
MNG24-8RX	49588	26-24	8	0.25	0.28	0.69	0.56	0.020	0.13	0.030	0.093	100	500
MNG24-8RK	00973	26-24	8	0.25	0.28	0.69	0.56	0.020	0.13	0.030	0.093	—	1000
MNG24-10RX	11321	26-24	10	0.25	0.28	0.69	0.56	0.020	0.13	0.030	0.093	100	500
MNG24-10RK	00974	26-24	10	0.25	0.28	0.69	0.56	0.020	0.13	0.030	0.093	—	1000



MNG24-0R

0


26-24



MNG24-2R

2


26-24



MNG24-4R

4


26-24



MNG24-6R

6


26-24



MNG24-8R

8

26-24



MNG24-10R

10

26-24

Stud Size
Wire Range